

Granville Hypafarm UTTO 10W/30

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypafarm UTTO is Specially formulated for modern multi speed electronically actuated transmissions fitted in Agricultural and Off highway equipment. Can be used for oil immersed brakes and as a hydraulic fluid where recommended.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

Allison: C4

Case: MS1204, MS1205 & MS1210

CAT: TO-2

Ford: WSS-M2C134-A, WSS-M2C134-B, WSS-M2C134-C, WSS-M2C134-D, WSS-M2C159-A, WSS-M2C41-B, WSS-M2C48-B, WSS-M2C53-A, WSS-M2C86-A, WSS-M2C86-B & WSS-M2C86-C
IMB6

John Deere: JDM 20A, JDM 20B, JDM 20C & JDM J27

Massey Ferguson: M1110, M1127, M1129A, M1135 & M1143

New Holland: 410-B & 420-A

Volvo: 97303 WB 101



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6514	5020618065142
199 Litre	6516	5020618065166

PRODUCT BENEFITS

*Ideal for agricultural and off highway applications

*Excellent heat transfer properties

PRODUCT USAGE

For use where this type and specification of oil is required

DIRECTIONS FOR USE

Use as per the component manufacturers recommendations



Granville Hypafarm UTTO 10W/30

20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance : Red Coloured liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

