

Granville Hammered Metal Paint – Brown

250ml Tin & 750ml Tin

PRODUCT DESCRIPTION

Granville Hammered Paint is an advanced, easy to use formulation – even on vertical surfaces – just apply like a conventional gloss paint. It gives an attractive and protective finish to all types of substrate. On ferrous substrates it provides a tough impermeable barrier to air and moisture which effectively seals out corrosion. Unlike currently available metal finish paints, it does not contain harmful solvents and has been designed to be slower drying making it easier and safer to use.

PRODUCT BENEFITS

- * Technologically advanced White Spirit formulation
- * Designed to protect, decorate and rejuvenate metal surfaces
- * Use for example on metal drainpipes, gates, ornaments, bicycles, garden furniture, vehicle chassis and on all types of industrial machinery
- * Simple one can treatment. No Undercoat, No Primer, No Rust
- * No special thinner required – just use white spirit
- * Easy to use – even on vertical surfaces – use like a conventional gloss paint

PRODUCT USAGE

Brush: Use a suitable sized brush, apply paint evenly using multi-directional strokes. Apply paint thickly and evenly then level out to avoid runs and sags.

Roller: Use a natural fibre roller. Cover the area evenly. Some thinning may be required (up to 5%)

Spray: Thin with white spirit. Apply multiple coats allowing paint to dry between coats. Use a gun pressure of 30-40 psi. Thin, depending on equipment used, by between 10-15%.

Use white spirit or turpentine substitute for thinning product and cleaning equipment.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
250ml Tin	4122	5020618041221
750ml Tin	4123	5020618041238



Granville Hammered Metal Paint – Brown

250ml Tin & 750ml Tin

DIRECTIONS FOR USE

On ferrous substrate it is recommended to wire brush and abrade to remove loose material and to provide a key. It is also recommended to wash the surface with detergent and water to remove any grease deposits.

On heavily rusted and pitted surfaces, first applying two coats of Granville Heavy Duty Rust Cure will improve the performance of the paint.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place away from direct sunlight.

SHELF LIFE

2 years from date of manufacture.

SPECIFICATION INFORMATION

Working temperature of cured product: -20°C to +100°C

Coverage: @100um DFT: 5-6 m²/ltr

Touch dry: 1.5 hours

Tack free: After 4 hours

Overcoating: After 12 hours

Salt spray: panels coated with Granville Metal Finish Paint will pass 1000 hours salt spray exposure to ASTM B117 when applied to the recommended film thickness of 100um.

Artificial weathering: After 600 hours exposure to ASTM G53-77 panels coated with Granville Metal Finish Paint will show minimal colour and gloss degradation.

Impact resistance: DIN55 669 Granville Metal Finish Paint, once cured, shows excellent impact resistance.

Appearance : Coloured thixotropic liquid



Granville Hammered Metal Paint – Brown

250ml Tin & 750ml Tin

Odour	: Characteristic – solvent
Specific Gravity	: 1.0 depending on colour
Solubility	: Insoluble in water
Flammability	: Flammable as a liquid
VOC	: VOC in g/l 2004/42/II1(i):600g/l(2007)/500g/l(2010). Product contains 400g/l

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

