

Granville FS-RX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville FS-RX 5W/30 is a high performance fully synthetic engine oil formulated for the latest Renault engines. This Mid SAPS oil is suitable for use in turbo charged petrol direct injection engines, Euro 6 diesel engines and is safe to use with vehicles fitted with exhaust emission after treatment devices. FS-RX 5W/30 offers excellent soot control and component protection.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3

Renault: RN17



* Image for illustrative purposes only.

PRODUCT BENEFITS

Mid SAPS formulation

Controls heat build up within the engine

Suitable for Euro 6 diesel engines

SIZE	PART NO	BARCODE
1 Litre	1178	5020618011781
5 Litre	1179	5020618011798
20 Litre	1180	5020618011804
199 Litre	1181	5020618011811

PRODUCT USAGE

For engines where this grade and specification is recommended.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed and upright in a cool dry place out of the reach of children.



Granville FS-RX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.3
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			75.6
Density	ASTM D792	@ 15°C			0.85
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7.5		10.6
HTHS Viscosity	ASTM D4683	mPa.s	>3.5		
NOACK Volatility	ASTM D5800	%		<11	
Viscosity Index	ASTM D2270				161

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

