Granville®
More than just an oil company

TECHNICAL DATA

Revision: 2 | Date: 11/11/2016

# 10k
# Engine Oil Treatment
300ml

## PRODUCT DESCRIPTION

10K Boost Engine Oil Treatment has been formulated to prevent the breakdown of engine oil additives caused by extreme heat and pressure thus reducing engine wear and promoting smooth and quieter engine running effectively prolonging the life of the engine oil. Engine oil must be changed in accordance with manufacturers service intervals. For use in petrol engines only.




* Image for illustrative purposes only.

## PRODUCT BENEFITS

* Protect engine from wear
* Effectively keeps engine clean
* Protects engine at cold start
* Promotes smoother and quieter engine running

| SIZE | PART NO | BARCODE |
|---|---|---|
| **300ml** | 1431 | 5020618014317 |

## PRODUCT USAGE

Add to engine oil at, or between, service intervals.

## DIRECTIONS FOR USE

Park on an even surface. Run engine to normal operating temperature, switch off engine, add contents of can and run for a further 5 minutes to ensure thorough mixing. Do not overfill engine. Use dipstick to check level.

## DOSAGE INFORMATION

One can treats 3-6 litres of engine oil.

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

**Granville Oil & Chemicals Ltd.**
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville®
More than just an oil company

# TECHNICAL DATA

Revision: 2 | Date: 11/11/2016

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

# 10k
# Engine Oil Treatment
**300ml**

## SHELF LIFE

3 years from date of manufacture.

| | | |
|---|---|---|
| **Appearance** | : | Amber liquid |
| **Odour** | : | Characteristic |
| **Solubility** | : | Insoluble in water |
| **Percentage of Base Oil** | : | Less than 70% |
| **Percentage of Biodiesel** | : | nil |

| Test | Method | Unit | Min. | Max. | Typical |
|---|---|---|---|---|---|
| Viscosity, Kinematic 100°c | ASTM D445 | $mm^2/s$ | 12.5 | <16.3 | |
| Viscosity, CCS | ASTM D4684 | mPa.s | | 7000 | |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

**Granville Oil & Chemicals Ltd.**
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com