



Granville

EV-8 0W/8

1 Litre, 5 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville EV-8 0W/8 is an ultra-low viscosity fully synthetic engine oil specially formulated for use in hybrid-electric (H.E.V) plug-in hybrid vehicles. (P.H.E.V) and battery electric vehicles (B.E.V) where this grade and specification of engine oil is recommended. This ultra-low viscosity oil is suitable for petrol engines, turbocharged or naturally aspirated with direct or indirect injection. Protects against low speed pre-ignition.

Refer to the owner's manual to ensure correct application.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SP-RC, SQ & SQ-RC
ILSAC: GF-6B

PRODUCT BENEFITS

- * Ultra-low viscosity fully synthetic engine oil
- * Excellent fuel economy
- * Protects against low speed pre-ignition (LSPI)

PRODUCT USAGE

Where recommended by the engine manufacturer

DIRECTIONS FOR USE

Use as per manufacturers recommendations

STORAGE INSTRUCTIONS

Store upright in a cool dry place out of the reach of children



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1194	5020618011941
5 Litre	1195	5020618011958
199 Litre	1197	5020618011972



Granville

EV-8 0W/8

1 Litre, 5 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: 80

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	4	6.1	
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
HTHS Viscosity	ASTM D4683	mPa.s	2.3		
NOACK Volatility	ASTM D5800	%		15	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

