Granville
Copper Grease
20g Tube, 70g Tube, 500g Tin, 3kg & 70g Norwegian



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville Copper Anti-Seize Compound is a soft copper coloured grease used to prevent seizure caused by metal to metal contact under arduous conditions. The product is both thermally and mechanically stable, very water repellent and will naturally adhere to metal surfaces.
Ensures excellent protection for metal parts against heat, seizure, rust, corrosion, water and acid.

PRODUCT BENEFITS

* Extremely long lasting
* Assists in assembly and dismantling
* Non melting
* Excellent corrosion inhibitor
* Extremely stable, both mechanically & thermally

SIZE	PART NO	BARCODE
20g Tube	0151	5020618001515
70g Tube	0148	5020618001485
500g Tin	0149	5020618001492
3kg	0155	5020618001553
70g Norwegian	1699	N/A

PRODUCT USAGE

Copper Grease is recommended for most applications where metal to metal contact needs to be avoided and for all assembly work where ease of dismantling is required including; keys, keyways, track adjusters and many more industrial and automotive uses.
Copper Grease is especially recommended for applications where lead content is unacceptable (present in many other anti-seize compounds).

DIRECTIONS FOR USE

Apply grease to the required surfaces to the recommended amount.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
Copper Grease
20g Tube, 70g Tube, 500g Tin, 3kg & 70g Norwegian

SHELF LIFE

5 years from date of manufacture.

SPECIFICATION INFORMATION

* Operating temperature range: -30°C to +1100°C
* Melting point: None (infusible product)
* Worked penetration: 280-320mm
* Un-worked penetration @ 25°C: 265-295mm
* NLGI classification: 2
* Co-efficient of friction: 0.11

Appearance	:	Gold/Copper smooth grease
Odour	:	Characteristic
Solubility	:	Insoluble in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com