

Granville FS-P 5W/30

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville FS-P 5W/30 is a new generation, fully synthetic multi-grade engine oil formulated to meet the performance demands of the latest low emission engines which combine high performance, fuel efficiency and emission control. Manufactured to a low SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C2 oil. Suitable for Peugeot, Citroen, Honda & Toyota engines.

NOTE: This Oil is NOT suitable for Vehicles that require Low Speed Pre-Ignition (LSPI) capabilities. Suitable for vehicles up to 2017.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2

PSA: B71 2290 (<2017)

API: SN/CF

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required

DIRECTIONS FOR USE

As recommended by the engine manufacturer.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0481	5020618004813
5 Litre	0482	5020618004820
20 Litre	0479	5020618004790



Granville FS-P 5W/30

1 Litre, 5 Litre & 20 Litre

STORAGE INSTRUCTIONS

Store upright and sealed in a cool, dry place out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.9
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			65.6
Density	ASTM D792	@ 15°C			0.85

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

