Granville
FS-P 5W/30
1 Litre, 5 Litre & 20 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville FS-P 5W/30 is a new generation, fully synthetic multi-grade engine oil formulated to meet the performance demands of the latest low emission engines which combine high performance, fuel efficiency and emission control. Manufactured to a low SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C2 oil. Suitable for Peugeot, Citroen, Honda & Toyota engines.
NOTE: This Oil is NOT suitable for Vehicles that require Low Speed Pre-Ignition (LSPI) capabilities. Suitable for vehicles up to 2017.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2
PSA: B71 2290 (<2017)
API: SN/CF
Fiat: 9.55535-S1

SIZE	PART NO	BARCODE
1 Litre	0481	5020618004813
5 Litre	0482	5020618004820
20 Litre	0479	5020618004790

PRODUCT BENEFITS

* Ensures lubricant performance over extended drain intervals
* Excellent high & low temperature performance
* Outstanding fuel efficiency
* Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
FS-P 5W/30
1 Litre, 5 Litre & 20 Litre

STORAGE INSTRUCTIONS

Store upright and sealed in a cool, dry place out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	11
Viscosity, CCS -30°c	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.9
Pour Point	ASTM D97	°c		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			67
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				156

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com