Burgess
Garden Furniture Woodsealer
1 Litre Trigger

PRODUCT DESCRIPTION

Burgess Garden Furniture Woodsealer has been developed to protect quality garden furniture, providing a tough coat with no noxious thinners. It can be applied with a brush or cloth and dries in around 20 minutes. There is no need to wait for perfect weather, it can be applied in damp conditions. Brushes may be washed in water. The product has a high resin content - so a little will go a long way - one litre will cover 15-20sq.m.

* Image for illustrative purposes only.

PRODUCT BENEFITS

* Quick drying
* Water based
* Allows timber to breathe

SIZE	PART NO	BARCODE
1 Litre Trigger	0821	5020618008217

PRODUCT USAGE

Ideal for use on exterior wooden garden furniture.

DIRECTIONS FOR USE

Timber to be coated should be free from all types of paint, varnish, wax, oil and grease. The surface may be damp but should be drying. Grey weathered wood need not be sanded. New or newly sanded oily woods (i.e. Teak) should be left to weather before application. Burgess Garden Furniture Woodsealer can be applied by brush, spray or soft cloth and it is recommended to apply a minimum of two coats. However on very porous timber more coats may be required. Marine Woodsealer will normally dry in 15 minutes, however additional coats may be applied before each coat has dried.
An air temperature of 5°C - 30°C is preferred, but avoid applying the product if the relative humidity is greater than 80% or when there is a risk of rain or heavy condensation during the drying period. When applying in confined spaces ensure sufficient air movement is available to remove excess moisture released during the drying process.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Burgess
Garden Furniture Woodsealer
1 Litre Trigger

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

SHELF LIFE

2 years from date of manufacture if stored unopened in the original container in a frost-free environment.

SPECIFICATION INFORMATION

Touch dry: 15 minutes
Coverage: 8m^2/l (dependent upon absorbency of substrate)

Appearance	:	Golden brown opaque liquid
Odour	:	Mild perceptible odour
Specific Gravity	:	1.04
Solubility	:	Miscible In water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com