



Granville FS-E 0W/20

1 Litre, 5 Litre, 25 Litre & 205 Litre

Product Description

Granville FS-E 0W/20 is an advanced fully synthetic low viscosity engine oil formulated for fuel efficiency. It provides excellent wear protection under the most extreme circumstances even at cold start up. This viscosity of oil may not be suitable for use in certain engine types, please refer to the owner manual or handbook.

Recommended for use by Granville for the following manufacturer's specifications

ILSAC: GF-4 & GF-5

API: SN

Chrysler: MS 6395

GM: 4718M, 6094M & Dexos 1 2015



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0693	5020618006930
5 Litre	0694	5020618006947
25 Litre	0695	5020618006954
205 Litre	0696	5020618006961

Product Benefits

*Fully synthetic low viscosity fuel efficient engine oil

*Ideal for petrol and hybrid engines

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Specification Information

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.848 @ 15.6°C (typical)
Solubility	:	Insoluble in water
Kinematic Viscosity @ 40°C	:	41.25 (Typical)
Kinematic Viscosity @ 100°C	:	7.77 (Typical)
Pour Point	:	-45°C





Granville FS-E 0W/20

1 Litre, 5 Litre, 25 Litre & 205 Litre

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 3 | Date: 24/01/2017

