



Granville Hypalube C3 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Granville Hypalube C3 fully synthetic engine oil has been specially formulated to meet the requirements of a Low SAPS (Sulphated Ash, Phosphorus and Sulphur) engine oil. Hypalube C3 is suitable for use in vehicles fitted with exhaust after treatment devices that recommend a lubricant of the grade and specification

Recommended for use by Granville for the following manufacturer's specifications

ACEA: C3
API: SN/CF
BMW: LL-04
GM: dexos 2™
MB: 229.31, 229.51 & 229.52
VW: 502.00, 505.00 & 505.01



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0526	5020618005261
5 Litre	0527	5020618005278
20 Litre	0564	5020618005643
199 Litre	0529	5020618005292

Product Benefits

- * Fully Synthetic Formulation
- * Long Life capabilities
- * Protects engine at optimum temperature and performance
- * For use with exhaust after treatment devices

Product Usage

Use as per the engine manufacturers recommendations

Directions for Use

Use as per the engine manufacturers recommendations

Storage Instructions

Store sealed in a cool, dry place

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.855 @ 15.6°C (typical)
Solubility	:	Insoluble in water
Flashpoint	:	> 200°C





Granville Hypalube C3 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Kinematic Viscosity @ 40°C : 71.28 cSt (typical)
Kinematic Viscosity @ 100°C : 12.09 cSt (typical)
Pour Point : -42°C

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 4 | Date: 24/01/2017

