



## Granville FS-GX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Granville FS-GX 5W/30 is a high performance fully synthetic engine oil that provides protection against low speed pre-ignition (LSPI) issues associated with smaller capacity turbo-charged engines. FS-GX is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

### Recommended for use by Granville for the following manufacturer's specifications

ILSAC: GF-5

GM: dexos1™ Gen 2

API: SN-RC, SN & SN Plus

### Product Benefits

- \* Helps resolve LSPI issues
- \* Fuel Efficient
- \* Fully Synthetic

### Directions for Use

Use as per manufacturer's recommendations

### Storage Instructions

Store upright in a cool dry place out of the reach of children

### Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Flammability	:	Non Flammable
Percentage of Base Oil	:	84.09
Percentage of Biodiesel	:	Nil



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	1140	5020618011408
5 Litre	1141	5020618011415
20 Litre	1142	5020618011422
199 Litre	1145	5020618011453





## Granville FS-GX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.37
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.28
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			61.51
Density	ASTM D792	@ 15°C			0.852

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

