

Granville Hypafleet LS E7 10W/40

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hypafleet LS E7 10W/40 a fully synthetic long drain heavy duty diesel engine oil featuring low SAPS (Sulphated Ash, Phosphorus and Sulphur) additive technology making it suitable for use with exhaust gas re-circulation (EGR), selective catalytic reduction (SCR) and diesel particulate Filters(DPF) exhaust after treatment devices. Suitable for use in vehicles meeting Euro I to Euro VI emission requirements.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E6, E7 & E9
API: CK-4
CAT: ECF-3
Cummins: 20081 & 20086
Ford: WSS-M2C171-F1
MAN: 3271-1 & 3575
MB: 228.51 & 228.31
Renault Truck: RLD-4
Volvo: VDS-4.5
Iveco: TLS E9

PRODUCT BENEFITS

- *Low SAPS (Sulphated Ash, Phosphorus and Sulphur)
- *Superior additive technology
- *Excellent performance under extreme conditions

PRODUCT USAGE

Use where this grade and specification is required

DIRECTIONS FOR USE

Follow engine manufacturers recommendations



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6458	5020618064589
199 Litre	6460	5020618064602



Granville Hypafleet LS E7 10W/40

20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and keep out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: 77.00%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.8	<16.3	
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	9		
Pour Point	ASTM D97	°C		-30	
HTHS Viscosity	ASTM D4683	mPa.s	3.9		
NOACK Volatility	ASTM D5800	%		12	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

