



Granville Hypafleet E5 10W/40

20 Litre & 199 Litre

Product Description

Hypalube Hypafleet E5 10W/40 meets a variety of requirements of European engine manufacturers in both normally aspirated and turbo engines working under difficult conditions, with extended drain period up to 60,000 kms (subject to specified operating conditions). Suitable for use in Euro II & III engine applications

Recommended for use by Granville for the following manufacturer's specifications

ACEA: A3/B3 & E5
 API: CH-4 & SL
 Cummins: 20071, 20072, 20076 & 20077
 MAN: 3275 & 3575
 MB: 228.3 & 229.1
 Renault Truck: RLD
 Volvo: VDS-3
 VW: 500.01 & 505.00



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	6486	5020618064862
199 Litre	6488	5020618064886

Product Benefits

- *Suitable for older engine types
- *Extended drain intervals
- *Latest technology additives and base oils

Product Usage

for use where this grade and specification is recommended by the engine manufacturer

Directions for Use

As per the manufacturers instructions

Storage Instructions

Store sealed and upright in a cool place and out of the reach of children

Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.87 @ 15.6°C (typical)
Solubility	:	Insoluble in water





Granville Hypafleet E5 10W/40

20 Litre & 199 Litre

Kinematic Viscosity @ 40°C	:	91.3 (Typical)
Kinematic Viscosity @ 100°C	:	13.5 (Typical)
Viscosity Index	:	150
Percentage of Base Oil	:	80.00%
Percentage of Biodiesel	:	Nil

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 0 | Date: 01/01/1970

