



Granville Hy-Vis Hydraulic 68

20 Litre & 199 Litre

Product Description

Hyalube Hy-Vis 68 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

Recommended for use by Granville for the following manufacturer's specifications

AFNOR: NF E 48603
David Brown: S1.53.101
Denison Filterability: TP021000
DIN: 51524 Part 2
Vickers: 1.286.S & 1.286.S3



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	0725	5020618007258
199 Litre	0009	5020618000099

Product Benefits

- *Excellent pumpability
- *Protects against oxidation and corrosion.

Storage Instructions

Store Upright and sealed in a cool place and out of the reach of children

Shelf Life

5 Years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	61.2	74.8	67.64
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s			8.79
Viscosity Index	ASTM D2270				0.874

Safety Precautions

Please see our latest EC Safety Data Sheets for details.





Granville Hy-Vis Hydraulic 68

20 Litre & 199 Litre

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 0 | Date: 01/01/1970

