



## Granville FS-MB 0W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

FS-MB 0W/40 is a fully synthetic high performing engine oil produced using the very latest in additive technology in combination with selected base oils. FS-MB 0W/40 is suitable for use in petrol and diesel engine both turbo charged and naturally aspirated including fuel injected and multivalve engine types.

### Recommended for use by Granville for the following manufacturer's specifications

ACEA: A3/B4

API: SN/CF

MB: 226.5 & 229.5

Porsche: A40

Renault: RN0700 & RN0710

VW: 502.00 & 505.00

Ford: WSS-M2C937-A



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	1174	5020618011743
5 Litre	1175	5020618011750
20 Litre	1176	5020618011767
199 Litre	1177	5020618011774

### Product Benefits

Excellent component protection  
Good High & low heat control

### Product Usage

Use where this specification and viscosity is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Store upright and sealed in a cool dry place and out of the reach of children.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Clear Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in Water





## Granville FS-MB 0W/40

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	13.81
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	10		10.6
Pour Point	ASTM D97	°C		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		<10	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			79.32
Density	ASTM D792	@ 15°C			0.845

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

