



Granville FS-B 5W/30

1 Litre, 5 Litre & 20 Litre

Product Description

FS-B 5W/30 is a fully synthetic low emission engine oil specially formulated using the very latest additive technology to produce a low SAPS lubricant. It provides excellent wear protection and is safe for use in vehicles where a diesel particulate filter is fitted.

Recommended for use by Granville for the following manufacturer's specifications

API: SN/CF
ACEA: C3
BMW: LL-04
MB: 229.31, 229.51 & 229.52
VW: 502.00, 505.00 & 505.01
GM: dexos 2™



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0593	5020618005933
5 Litre	0594	5020618005940
20 Litre	0588	5020618005889

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil





Granville FS-B 5W/30

1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.47
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7		7.98
Pour Point	ASTM D97	°C		-36	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			63.03
Density	ASTM D792	@ 15°C			0.854

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

