



Granville FS-F 5W/30

1 Litre & 5 Litre

Product Description

Granville FS-F 5W/30 is an advanced fully synthetic engine oil formulated from quality base oils and the most up to date additives. It provides excellent wear protection and is safe for use in vehicles that have a diesel particulate filter fitted.

Recommended for use by Granville for the following manufacturer's specifications

ACEA: A5/B5

Ford: WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C & WSS-M2C913-D

STJLR: 03.5003

API: SL/CF



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0508	5020618005087
5 Litre	0509	5020618005094

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water



Granville FS-F 5W/30

1 Litre & 5 Litre



Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.9
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°c		-27	
NOACK Volatility	ASTM D5800	%		13	
Total Base Number	ASTM D2896	mg KOH/g	10		10.6
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			65
Density	ASTM D792	@ 15°C			0.855

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

