

Granville FS-D 5W/40 25 Litre



Product Description

Granville FS-D 5W/40 is a fully synthetic diesel oil with an extended drain capability of up to 24,000 Km (subject to manufacturers recommendation) allowing for the variable service intervals of many modern diesel engines. This oil is NOT suitable for vehicles that have diesel particulate filters fitted.

Recommended for use by Granville for the following manufacturer's specifications

API: CF
ACEA: B3/B4
VW: 502.00 & 505.00
BMW: LL-01
MB: 229.3



* Image for illustrative purposes only.

Size	Part No	Barcode
25 Litre	0215	5020618002154

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.852 @ 15.6°C (typical)
Solubility	:	Insoluble in water
Flashpoint	:	>200°C





Granville FS-D 5W/40 25 Litre

Kinematic Viscosity @ 40°C : 81.6 cSt (typical)

Kinematic Viscosity @ 100°C : 13.3 cSt (typical)

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 1 | Date: 16/03/2012

